

SURFACE DELAY



Toll Free - 1.800.544.8488
www.SureCreteDesign.com
www.TheConcreteWhisperer.com

Technical Data

Coverage:

approx. 200 –400 sq. ft. per gallon.

Appearance:

Milky, opaque color

Odor:

Solvent

Shelf Life:

1 year

Packaging:

5 gallon pail
1 gallon jug

Storage:

Containers should be properly stored. Prevent accumulation of water, dirt or other residue on covers. Protect from freezing.

Clean up:

Rinse tools & pump-up sprayer with water.

DESCRIPTION

Surface Delay is a transparent blue, soapy odor, non-hazardous, concentrated, film-forming solution that is designed to retard the initial evaporation of water from freshly placed concrete or stamp overlay during finishing operations. **Surface Delay** is especially effective for conditions that include high wind, low humidity, high temperature or any combination. Concrete can be placed with a lower slump, even under rapid drying conditions, helping to reduce related shrinkage cracking or surface checking by slowing initial evaporation of bleed water.

APPLICATION

Preparation: **Surface Delay** must diluted with water at 9:1 (water/ concentrate) ratio. One gallon (3.8 L) of **Surface Delay**, properly diluted with water, will provide 10 gallons (37.8 L) of finished product

Methods: Place the concrete or stamp overlay in the conventional manner and screed the entire surface to level—or gauge rake stamp overlay. Spray properly mixed **Surface Delay** on the entire surface in a continuous and consistent pattern with a pump-up sprayer. During finishing operations **Surface Delay** must be trowelled into the concrete surface or sprayed ahead of smoother on stamp overlay. It must be worked into the surface. **Surface Delay** can be reapplied between finishing operations under severe conditions.

PRECAUTIONS

- Keep out of reach of children.
- Avoid inhalation of vapors. Ensure adequate ventilation.
- Avoid contact with skin. Protective clothing is recommended. Thoroughly wash with soap & water.
- Wear protective eyewear. Avoid splashing & spraying in eyes. Flush with copious amounts of water if accidental contact occurs.
- Avoid ingestion. Get medical help.

LIMITATIONS

Surface Delay is not a substitute for curing compounds. This product is effective only during placing and finishing operations. **Surface Delay** is not a surface retarder. Do not apply during final troweling, discoloration may occur.

WARRANTY

Warranty of this product, when used according to the directions, is limited to refund of purchase price, or replacement of product (if defective), at manufactures/seller's option. SureCrete Design Products shall not be liable for cost of labor or direct and/or incidental consequential damages.

